

ST-2000

INNOVATION AND PERFORMANCE

- Its unique design lets you work in a variety of floor conditions maintaining maximum traction
- Full width construction and innovative tread design offers an increased footprint
- Reduced wear and low rolling resistance
- High resistance to torsion, keeping heat build up to a minimum.
- Also available in "Talon" (self-locking eliminating lock ring and flange), Non Marking White and Anti-Static versions



APPLICATIONS:	CUSTOMER NEEDS:	
Fork lifts	Comfort	● ● ● ● ●
Side Loaders	Load Capacity	● ● ● ● ●
Skid Steer	Rolling Resistance	● ● ● ● ●
Ports	Stability	● ● ● ● ●
Ground Support Equipment	Abrasion Resistance	● ● ● ● ●
	Return on Investment	● ● ● ● ●
	Puncture Proofing	● ● ● ● ● ●
	Speed and Distance	● ● ● ●



TECHNICAL SPECIFICATIONS:

Size	Rim	Tread Pattern	Tyre Load Capacity					Nominal Sizing	
			Fork lifts Max. Speed 16mph/25km/h		6 km/h	Other Vehicles (kg)		Width (mm)	Outer Diam. (mm)
			Load Wheel (kg)	Steer Wheel (kg)		10 km/h	25 km/h		
4.00-8	*3.00-8	ST2/RAIADO	950	730	950	860	730	105	406
15x4 ^{1/2} -8 (125/75-8)	*3.00-8	ST2	1040	800	1040	945	800	104	376,5
5.00-8	*3.00-8	ST2	1415	1090	1415	1285	1090	123	456
5.00-8	*3,25-8	ST2	1415	1090	1415	1285	1090	123	456
16x6-8 (150/75-8)	*4.33R-8	ST2	1455	1120	1455	1320	1120	144	404,6
18x7-8 (180/70-8)	*4.33R-8	ST2	2145	1650	2145	1945	1650	143	452
18x7-8 (180/70-8)	3.00R-8	ST2	2145	1650	2145	1945	1650	143	452
6.00-9	*4.00E-9	ST2	1885	1450	1885	1710	1450	144	520
6.00 - 15	*4.50-15	ST2	3545	2725	3545	3215	2725	187	726
21x8-9	*6.00E-9	ST2	2755	2120	2755	2500	2120	179	524,5
6.50-10	*5.00F-10	ST2	2340	1800	2340	2125	1800	157,5	571
200/50-10	*6.50F-10	ST2	2470	1900	2470	2240	1900	179	454
23x9-10 (225/75-10)	*6.50F-10	ST2	3445	2650	3445	3125	2650	209,5	576
23x9-10 (225/75-10)	*5.00F-10	ST2	3445	2650	3445	3125	2650	209,5	576
23x10-12	*8.00-10	ST2	3770	2900	3770	3420	2900	222	585
7.00-12	*5.00S-12	ST2	2920	2240	2920	2645	2240	168	651
7.00-15	*5.50-15	ST2	3545	2725	3545	3215	2725	187	726
27x10-12	*8.00G-12	ST2	3900	3000	3900	3540	3000	222,5	671
28x9-15	*7.0-15	ST2	3770	2900	3770	3420	2900	207,8	681
7.50-15	*5,5-15	ST2	3900	3000	3900	3540	3000	187	758
7.50-15	*6,5-15	ST2	3900	3000	3900	3540	3000	187	758
8.25-15	*5,5-15	ST2	4745	3650	4745	4305	3650	208	817
8.25-15	*6,5-15	ST2	4745	3650	4745	4305	3650	208	817
250-15 (250/70-15)	*7.0-15	ST2	4745	3650	4745	4305	3650	217,5	715
250-15 (250/70-15)	*7.5-15	ST2	4745	3650	4745	4305	3650	217,5	715
300-15	*8.0-15	ST2	5850	4500	5850	5310	4500	242,5	822
350-15 (355/65-15)	*9,75-15	ST2	7800	6000	7800	7080	6000	297	822