

# ST-3000

## THE MOST RECENT TECHNOLOGY IN INDUSTRIAL SOLID TYRES

- Designed to match the high standards being set by the new generation of fork lift trucks
- Offers maximum stability under high loads, whilst maintaining low heat build up and optimum resilience for enhanced driver comfort.
- Our advanced three compound technology offers maximum abrasion resistance in tough conditions
- Optimized cost per hour ratios, thus reducing downtime
- Also available in “Talon” (self-locking eliminating lock ring and flange), Non Marking White and Anti-Static versions



### APPLICATIONS:

Fork lifts  
Side Loaders  
Skid Steer  
Ports  
Ground Support  
Equipment

### CUSTOMER NEEDS:

Comfort	● ● ● ● ● ●
Load Capacity	● ● ● ● ● ●
Rolling Resistance	● ● ● ● ● ●
Stability	● ● ● ● ● ●
Abrasion Resistance	● ● ● ● ● ●
Return on Investment	● ● ● ● ● ●
Puncture Proofing	● ● ● ● ● ●
Speed and Distance	● ● ● ● ● ●



### TECHNICAL SPECIFICATIONS:

Size	Rim	Tread Pattern	Tyre Load Capacity					Nominal Sizing	
			Fork lifts Max. Speed 16mph/25km/h		Other Vehicles (kg)			Width (mm)	Outer Diam. (mm)
			Load Wheel (kg)	Steer Wheel (kg)	6 km/h	10 km/h	25 km/h		
5.00-8	*3.00-8	ST3	1415	1090	1415	1285	1090	124	446,5
5.00-8	*3.25-8	ST3	1415	1090	1415	1285	1090	124	446,5
18x7-8 (180/70-8)	*4.33R-8	ST3	2145	1650	2145	1945	1650	145	452
16x6-8 (150/75-8)	*4.33R-8	ST3	1455	1120	1455	1320	1120	140	405,5
15x4,5-8 (125/75-8)	*3.00R-8	ST3	1040	800	1040	945	800	111	374,5
140/55-9	*4.00R-9	ST3	1170	900	1170	1060	900	130,5	379
18x7-8 (180/70-8)	3.00R-8	ST3	2145	1650	2145	1945	1650	145	452
23x9-10 (225/75-10)	*6.50R-10	ST3	3445	2650	3445	3125	2650	199	565
23x9-10 (225/75-10)	5.00R-10	ST3	3445	2650	3445	3125	2650	199	565
23x10-12 (250/60-12)	*8.00R-12	ST3	3770	2900	3770	3420	2900	245	575
21x8-9	*6.00R-9	ST3	2755	2120	2755	2500	2120	190,2	524
200/50-10	*6.50R-10	ST3	2470	1900	2470	2240	1900	194,2	449,5
27x10-12	*8.00R-12	ST3	3900	3000	3900	3540	3000	247	659,5
6.00-9	*4.00E-9	ST3	1885	1450	1885	1710	1450	136,7	525
6.50-10	*5.00F-10	ST3	2340	1800	2340	2125	1800	151,4	568,5
7.00-12	*5.00S-12	ST3	2910	2240	2910	2645	2240	169	657,3
28x9-15	*7.0-15	ST3	3770	2900	3770	3420	2900	206	689,5
28x12.5-15 (355/45-15)	*9.75 - 15	ST3	5040	3875	5040	5945	5040	292	683
7.00-15	*5.5-15	ST3	3545	2725	3545	3215	2725	167,5	714
7.00-15	*6.0-15	ST3	3545	2725	3545	3215	2725	167,5	714
8.25-15	5.5-15	ST3	4745	3650	4745	4305	3650	208	805
8.25-15	*6.5-15	ST3	4745	3650	4745	4305	3650	208	805
8.25-15	6.5-15	ST3 / LISO	4745	3650	4745	4305	3650	222,8	807
250-15 (250/70-15)	*7.5-15	ST3	4745	3650	4745	4305	3650	210	709
250-15 (250/70-15)	*7.0-15	ST3	4745	3650	4745	4305	3650	210	709
300-15	*8.0-15	ST3	5850	4500	5850	5310	4500	250,5	809
350-15 (355/65-15)	*9.75-15	ST3	7800	6000	7800	7080	6000	299,5	813